

**SUGGESTED SPECIFICATIONS  
LIFTMOORE MODEL 3660X and 3660XP CRANES**

**CAPACITY:** Moment rating of 36,000 Ft.-Lbs. with capacities as follows:

*6000 Lbs.	at	6 Ft.
*4500 Lbs.	at	8 Ft.
*3600 Lbs.	at	10 Ft.
3000 Lbs.	at	12 Ft.
2250 Lbs.	at	16 Ft.
2000 Lbs.	at	18 Ft.
1800 Lbs.	at	20 Ft.

\* Use traveling block, double line for loads above 3000 Lbs.

**HOIST WINCH:** The hoist winch is a worm gear design with a 38:1 gear ratio. The safety brake includes a one way clutch that releases the brake when lifting the load. The winch drum to wire rope ratio is 17:1 as required by ASI. The winch is powered by a low speed, high torque hydraulic motor. Line speed is 19 FPM with 6 GPM input. The hoist winch is mounted on the boom.

**WIRE ROPE AND SHEAVES:** The 3660 crane is supplied with 95 Ft. of 3/8 In. 7 X 19 galvanized aircraft cable. Minimum breaking strength of the cable is 14,400 Lbs. and meets ANSI requirements. Wire rope is outside of the boom and clearly visible for operator's inspection. A 3 ton capacity swivel traveling block assembly with roller thrust bearing and safety latch is included.

**HYDRAULIC SYSTEM:** All crane functions are hydraulically powered by an engine driven hydraulic pump. The PTO, pump, reservoir and hoses are not supplied with the crane. Flow and pressure requirements are 6 GPM and 2750 PSI. For smooth operation and minimum heat buildup a pressure compensated flow control system is used. The system will not build up pressure above the level required to operate a function. This reduces the heat buildup in the oil and the power required from the engine. A parallel control circuit is used.

Proportional hydraulic control is available as an option (model 3660XP). This control system gives the operator of the crane variable speed control of each crane function. All functions are controlled through the remote pendant. Manual override control is provided for directional control of each hydraulic function.

**ROTATION:** Rotation is 360 degree continuous and unlimited. A gear bearing supports the crane. Crane rotation is powered by a 45:1 ratio worm gear box with integral low speed, high torque hydraulic motor. Rotation will be restricted on models with auxiliary electric controls.



**BOOM ELEVATION:** A 4.5 In. bore hydraulic cylinder elevates the boom from -5 degrees to +75 degrees. A counterbalance valve is mounted integral with the cylinder. This valve has three vital purposes. It will hold the load in the event of a hose failure, control the rate of descent when powered down, and relieve the cylinder from high pressure.

**BOOM EXTENSION:** The boom is extended hydraulically from 10 Ft. to 16 Ft. by a 3 In. bore hydraulic cylinder and is extended manually from 16 Ft. to 20 Ft. The extension cylinder is mounted inside the boom for protection. For safety a counterbalance valve is mounted in the cylinder. The power extendable portion of the boom slides on Nylatron slide pads for minimum friction.

**PENDANT CONTROL:** A 25 Ft. remote pendant control is supplied with each crane. For safest possible use, the pendant control is removable from the crane and each function is controlled by a momentary contact toggle switch.

**LOAD SENSOR:** A load limiting sensor is installed in the elevation cylinder. This sensor will shut down hoist up, boom out, and boom down when an overload is detected. The sensor will reset after the load is lowered.

**ANTI-TWO BLOCK:** The 3660 includes an anti-two block feature that prevents extending the boom against the traveling block and breaking the cable.

**MOUNTING:** Four 7/8 In. grade 8 bolts are required. Bolts are not included. The crane mounts on a 16.75 In. square base plate with a 14.75 In. square bolt pattern.

**ACCESSORIES:** An outrigger is necessary to keep the truck as level as possible as well as reducing the load on the crane's rotation mechanism and the truck's suspension components. Jackstands are also available for stability of the truck. A boom rest is required to support the crane while the truck is in motion. Liftmoore can supply all of these options.

**CHASSIS:** Minimum chassis size for mounting the 3660 is 14,500 Lbs. GVWR.

<b>WEIGHT:</b>	3660X-16	1755 Lbs.	3660XP-16	1820 Lbs.
	3660X-20	1830 Lbs.	3660XP-20	1870 Lbs.



*Providing lifting solutions  
for every need*

**pmindustries.ca**

**Toll Free: 1-855-656-1689**



HOUSTON, TEXAS  
FAX: (800) 824-5559 (USA & Canada)  
FAX: (713) 688-6324  
PHONE: (713) 688-5533  
[www.liftmoore.com](http://www.liftmoore.com)